

RBMTX-Lite-IO

THE SMALLEST, LOW COST GSM/UMTS/LTE ROUTERS

TELEORIGIN
UNIQUE TECHNOLOGY FOR TELEMETRY

The RBMTX-Lite-IO is a low-cost, very small router made for wireless m2m applications. It is a compact device which supports 3G or 4G, WiFi*, Bluetooth*, Ethernet networks and RS232/RS485, GPIO, Dual SIM and USB interfaces.

* - option



THE RBMTX-LITE-IO ROUTER SERIES

Router is dedicated for users looking for easy and robust mobile Internet access. Internet connection is easily available and configurable via internet browser without any need of installing software or drivers for the device.



RBMTX-Lite-IO is a universal solution for all low-volume M2M/IoT and mobile data applications including metering, traffic systems, transportation and logistics, security, vending machines and facility management.

KEY BENEFITS



FAST TIME TO-MARKET



BEST PRICING
LEVEL

EXTENDED POWER
SUPPLY RANGE



EASY WIRELESS
APPLICATION



LOW POWER
CONSUMPTION



FEATURES

Ethernet 10/100 Mbps
3G/4G modem
RS232/RS485 interfaces
WiFi 2.4 GHz + Bluetooth 3.0/4.1 option
Dual SIM
4 x Inputs + 2 x outputs
Embedded Linux platform
Ports forwarding, IPsec, OpenVPN

SPECIFICATION:

- Small, robust and very cost-effective router
- Easy to use configuration via web interface
- Ethernet 10/100 Mbit/s | RS232 | RS485
- OpenVPN, IPsec, etc.
- 4G Cat. 4 or Cat. 1 modem B1/B3/B7/B8/B20@LTE, 900/2100MHz@UMTS, 900/1800@GSM
- 3G modem 900/2100MHz@UMTS, 900/1800MHz@GSM

- Dual SIM for roaming scenarios
- Wi-Fi/Bluetooth interface (option)
- TCP/IP, E-mail protocols, SMS
- Python, "C" or Bash-script programmable
- Modbus RTU - Modbus TCP gateway/converter
- Extremely compact (83 x 60 x 34 mm with connectors)
- Rugged metal housing
- Also available as a programmable Linux platform

OPTIONAL ACCESSORIES:

- External antenna
- Power supply and customized connection
- DIN mounting
- Wall mounting

| Network | Model | Speed max. | Interface | | | Ethernet | WiFi Bluetooth | Dual SIM | GPIO |
|---------------------|-------------------------------|------------------|-----------|-------|-----|----------|-------------------|----------|-------------------|
| | | | RS232 | RS485 | USB | | | | |
| 4G Cat. 4 | RBMTX Lite-IO 4G Cat. 4 | 150/50 Mbit/s | • | • | • | • | ○ | • | 4 x IN 2 x OUT |
| 4G Cat. 1 | RBMTX Lite-IO 4G Cat. 1 | 10/5 Mbit/s | • | • | • | • | ○ | • | 4 x IN 2 x OUT |
| 3G | RBMTX Lite-IO 3G | 7.2 Mbit/s | • | • | • | • | ○ | • | 4 x IN 2 x OUT |

• support ○ option - not support